

## TECHNICAL DATASHEET

SAP No. 30016217 Article Description SAERcore 300/RC25/300 - 1250mm

Textile Structure 7011065 SAERcore®

### ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
3	CSM	300 g/m <sup>2</sup>	+/- 10,0 %	E-glass
2	Core	250 g/m <sup>2</sup>	+/- 10,0 %	Recycled Synthetic Core
1	CSM	300 g/m <sup>2</sup>	+/- 10,0 %	E-glass
Stitching		7 g/m <sup>2</sup>	+/- 2 g/m <sup>2</sup>	Polyamid 6.6 122 dtex

Fiber input can be determined individually

### FURTHER CHARACTERISTICS

Gauge	3,5	Stitching pattern	tricot	Width (nominal)	1250 mm
Stitch length	5,00 mm	Total tolerance	+/- 10,2 %	Total areal weight	857 g/m <sup>2</sup>

Labelling (Standard)	Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.
Packaging (Standard)	Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.
Storage (recommendation)	Keep in original packaging. Store in a dry environment. Avoid direct sunlight. Fabrics to be kept under processing conditions at least 24 hours prior to use to avoid problems with humidity and electrostatic charge.
Important advice	The Z side of the stitching line should be place preferably on the cosmetic face to obtain the best surface finish.

SAERTEX France SAS has been certified in accordance with ISO 9001:2015.