

## TECHNICAL DATASHEET

SAP No. 30001973 Article Description SFEP-12g/m<sup>2</sup>-130mm

Textile Structure 7002659 SAERfix<sup>®</sup> EP

### ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
1	Glue	12 g/m <sup>2</sup>	+/- 16,0 %	SAERfix EP

Paper is the supporting medium of the glue.

### FURTHER CHARACTERISTICS

Width	130 mm	Total tolerance	+/- 16,0 %	Total areal weight	12 g/m <sup>2</sup>
-------	--------	-----------------	------------	--------------------	---------------------

**Labelling (Standard)** Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

**Packaging (Standard)** Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

**Storage** With original packaging: No moisture recommendation and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.

**Important advice** Storage temperatur: max. 30°C, no direct sunlight. Adhesiveness of SAERfix<sup>®</sup> EP is guaranteed within 4 months of production date.