TECHNICAL DATASHEET

SAP No. **30001763** **Article Description** **Y-E-1217g/m²-1270mm**

Textile Structure 7000033 **SAERTEX®**

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
3	0 °	709 g/m²	+/- 5 %	E-glass 2.400 TEX
2	45 °	251 g/m²	+/- 5 %	E-glass 300 TEX
1	-45 °	251 g/m²	+/- 5 %	E-glass 300 TEX
Stitching		6 g/m²	+/- 1 g/m²	PES [Polyester] 76 dtex

Fiber input can be determined individually

FURTHER CHARACTERISTICS

Gauge	5,0	Stitching pattern	tricot-warp	Width (nominal)	1.270 mm
Stitch length	2,60 mm	Total tolerance	5,1 %	Total areal weight	1217 g/m²

Labelling (Standard)	Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.
Packaging (Standard)	Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.
Storage recommendation	With original packaging: Temperature 15-35°C and 20-80% humidity. No moisture and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.