

B

Page 1 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

SAERfix® EP on Siliconpaper

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

See definition of the substance or mixture.

Industrial use

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(B)

SAERTEX GmbH & Co. KG, Brochterbecker Damm 52, 48369 Saerbeck, Germany Phone: +49 (0) 2574 902 0, Fax: +49 (0) 2574 902 9 info@saertex.com, www.saertex.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (SAR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

This is an article.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

This is an article.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients



Page 2 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 23.03.2017 / 0002 Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

3.1 Substance

n.a. **3.2 Mixture**

Reaction products of diglycidyl ether bisphenol F (DGEBF) and	
oligomeric phenol diglycidyl ethers with acrylic acid	
Registration number (REACH)	01-2119521533-48-XXXX
Index	
EINECS, ELINCS, NLP	700-487-6 (REACH-IT List-No.)
CAS	
content %	50-70
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Skin Sens. 1B, H317
	Aquatic Chronic 2, H411

reaction product bisphenol A-(epichlorhydrin), epoxy resin	
(number average molecular weight <= 700)	
Registration number (REACH)	01-2119456619-26-XXXX
Index	603-074-00-8
EINECS, ELINCS, NLP	500-033-5 (NLP)
CAS	25068-38-6
content %	25-50
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319
	Skin Irrit. 2, H315
	Skin Sens. 1, H317
	Aquatic Chronic 2, H411

2-Propenenitrile, polymer with 1,3-butadiene, carboxy-terminated, polymers with bisphenol A and epichlorohydrin	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	68610-41-3
content %	25-45
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315
	Skin Sens. 1, H317
	Eye Irrit. 2, H319
	Aquatic Chronic 2, H411

Reaction product: Bisphenol-A-Epichlorhydrin resins with average molecular weight > 700	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	25036-25-3
content %	10-25
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319
	Skin Irrit. 2, H315
	Skin Sens. 1, H317

Epoxide resin	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	25085-99-8
content %	2,5-10



Page 3 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

Classification according to Regulation (EC) 1272/2008 (CLP)

Eye Irrit. 2, H319

Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Supply person with fresh air.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

None known

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

No special measures required.

Avoid contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.



(B)

Page 4 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Protect from direct sunlight.

Store in a dry place.

Do not store over 30°C.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

© Chemical Name	Cellulose			Content %:
WEL-TWA: 10 mg/m3 (Cellulos	e, total inh. dust),	WEL-STEL:	20 mg/m3 (Cellulose, total inh. dust)	
4 mg/m3 (Cellulose, respirable)				
Monitoring procedures:	-			
BMGV:			Other information: -	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

reaction product bisphenol A-(epichlorhydrin), epoxy resin (number average molecular weight <= 700)									
Area of application	n Exposure route / Effect on health Descripto Value Unit Note								
	Environmental		r						
	compartment								
	Environment - freshwater		PNEC	0,003	mg/l				
	Environment - marine		PNEC	0,0003	mg/l				



Œ

Page 5 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

	Environment - water, sporadic (intermittent)		PNEC	0,018	mg/l
	release Environment - sewage		PNEC	10	mg/l
	treatment plant				
	Environment - sediment, freshwater		PNEC	0,5	mg/kg dw
	Environment - sediment, marine		PNEC	0,5	mg/kg dw
	Environment - soil		PNEC	0,05	mg/kg dw
	Environment - oral (animal feed)		PNEC	11	mg/kg
Consumer	Human - dermal	Short term, systemic effects	DNEL	3,571	mg/kg bw/day
Consumer	Human - oral	Short term, systemic effects	DNEL	0,75	mg/kg bw/day
Consumer	Human - oral	Long term, systemic effects	DNEL	0,75	mg/kg bw/day
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,75	mg/m3
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,75	mg/m3
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	8,33	mg/kg bw/day
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	12,25	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	12,3	mg/m3

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Normally not necessary.

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Normally not necessary.

If applicable

Nitrile-soaked cotton gloves with CE sign EN 374)

Leather gloves



Page 6 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Solid

Colour: According to specification

Odour: Characteristic
Odour threshold: Not determined

pH-value: n.a.

Melting point/freezing point:

Not determined
Initial boiling point and boiling range:

Not determined

Flash point: n.a.

Evaporation rate: Not determined Flammability (solid, gas): Not determined

Lower explosive limit:

Upper explosive limit:

Vapour pressure:

Na.

Vapour density (air = 1):

n.a.

n.a.

Density:

Bulk density:

Not determined
Solubility(ies):

Not determined
Water solubility:

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Not determined
Not determined
Not determined
Not determined

Viscosity:

Explosive properties: Product is not explosive.

Oxidising properties: No

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Surface tension:

Solvents content:

Not determined
Not determined
Not determined
Not determined
Not determined

SECTION 10: Stability and reactivity



Œ

Page 7 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

10.1 Reactivity

Not to be expected

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

None known

10.5 Incompatible materials

None known

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

SAERfix® EP on Siliconpape	r		,	,		
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Reaction products of diglyci	Reaction products of diglycidyl ether bisphenol F (DGEBF) and oligomeric phenol diglycidyl ethers with acrylic acid						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute		
					Oral Toxicity - Acute		
					Toxic Class Method)		
Skin corrosion/irritation:				Human being	Regulation (EC)	Irritant	
					440/2008 B.46 (IN		
					VITRO SKIN		
					IRRITATION -		
					RECONSTRUCTED		
					HUMAN EPIDERMIS		
					MODEL TEST)		
Serious eye				Rabbit	OECD 405 (Acute	Not irritant	
damage/irritation:					Eye		
					Irritation/Corrosion)		



Page 8 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 23.03.2017 / 0002
Replacing version dated / version: 21.03.2016 / 0001
Valid from: 23.03.2017

PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

Respiratory or skin	Mouse	OECD 429 (Skin	Yes (skin
sensitisation:		Sensitisation - Local	contact)
		Lymph Node Assay)	,

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Positive
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicit y Studies)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	50	mg/kg bw/d			
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	100	mg/kg bw/d			
Symptoms:						diarrhoea, weight loss

Reaction product: Bisphenol-A-Epichlorhydrin resins with average molecular weight > 700										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Skin corrosion/irritation:						Irritant				
Serious eye						Irritant				
damage/irritation:										
Respiratory or skin						Sensitising				
sensitisation:										

Epoxide resin												
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes						
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat								
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rabbit								
route:												
Respiratory or skin				Human being		Sensitising						
sensitisation:						(skin contact)						
Carcinogenicity:						Negative						

Cellulose										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Acute toxicity, by oral route:	LD50	>3000	mg/kg	Rat						
Acute toxicity, by inhalation:	LC50	5800	mg/m3/4	Rat						
			h							
Skin corrosion/irritation:						Not irritant				
Serious eye						Not irritant				
damage/irritation:										



Page 9 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001 Valid from: 23.03.2017

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

Respiratory or skin sensitisation:			Not sensitizising
Germ cell mutagenicity:			No indications of such an effect.
Carcinogenicity:			No indications of such an effect.
Symptoms:			mucous membrane irritation

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

SAERfix® EP on Siliconpaper											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to fish:							n.d.a.				
12.1. Toxicity to							n.d.a.				
daphnia:											
12.1. Toxicity to algae:							n.d.a.				
12.2. Persistence and							n.d.a.				
degradability:											
12.3. Bioaccumulative							n.d.a.				
potential:											
12.4. Mobility in soil:							n.d.a.				
12.5. Results of PBT							n.d.a.				
and vPvB assessment											
12.6. Other adverse							n.d.a.				
effects:											

Reaction products of o	Reaction products of diglycidyl ether bisphenol F (DGEBF) and oligomeric phenol diglycidyl ethers with acrylic acid											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes					
12.1. Toxicity to fish:	LC50	96h	2,2	mg/l	Brachydanio rerio	OECD 203						
						(Fish, Acute						
						Toxicity Test)						
12.1. Toxicity to	EC50	48h	55	mg/l	Daphnia magna	OECD 202						
daphnia:						(Daphnia sp.						
						Acute						
						Immobilisation						
						Test)						
12.1. Toxicity to algae:	EC50	72h	8	mg/l	Desmodesmus	OECD 201						
					subspicatus	(Alga, Growth						
						Inhibition Test)						
Toxicity to bacteria:	EC50	3h	594	mg/l	activated sludge	OECD 209						
						(Activated						
						Sludge,						
						Respiration						
						Inhibition Test						
						(Carbon and						
						Ammonium						
						Oxidation))						

reaction product bispl	reaction product bisphenol A-(epichlorhydrin), epoxy resin (number average molecular weight <= 700)									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			



GB)

Page 10 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

12.1. Toxicity to fish:	LC50	96h	1,2	mg/l	Oncorhynchus mykiss	U.S. EPA ECOTOX Database	
12.1. Toxicity to daphnia:	EC50	48h	1,1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	9,4	mg/l	Selenastrum capricornutum	U.S. EPA ECOTOX Database	
12.2. Persistence and degradability:		28d	5	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		3,8			,	

Reaction product: Bisphenol-A-Epichlorhydrin resins with average molecular weight > 700												
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes					
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		Analogous conclusion					
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna		Analogous conclusion					
12.1. Toxicity to algae:	EC50	72h	>100	mg/l			Analogous conclusion					

Epoxide resin										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	LC50		1,5-7,7	mg/l	Oncorhynchus mykiss					
12.1. Toxicity to fish:	LC50		3,1	mg/l	Pimephales promelas					
12.1. Toxicity to fish:	LC50		9,4	mg/l	Brachydanio rerio					
12.1. Toxicity to daphnia:	EC50		1	mg/l	Daphnia magna					
12.1. Toxicity to algae:	IC50		18	mg/l	Selenastrum capricornutum					
12.2. Persistence and degradability:		28d	2-3	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)				
12.3. Bioaccumulative potential:	Log Pow		2,8-4			,				

Cellulose							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:							No

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:



Page 11 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 03 06 organic wastes other than those mentioned in 16 03 05

Recommendation:

Pay attention to local and national official regulations.

Implement substance recycling.

For contaminated packing material

Pay attention to local and national official regulations.

Cleaned packaging:

Recycling

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.Hazard identification number:n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 8, 15



Page 12 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H317 May cause an allergic skin reaction.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation

Skin Sens. — Skin sensitization

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Eye Irrit. — Eye irritation

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIHAmerican Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency



Page 13 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAELLowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

ppm parts per million PROC Process category PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)



Page 14 of 14

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2017 / 0002

Replacing version dated / version: 21.03.2016 / 0001

Valid from: 23.03.2017 PDF print date: 28.03.2017 SAERfix® EP on Siliconpaper

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.