

## TECHNICAL DATASHEET

<b>SAP No.</b>	<b>20395</b>	<b>Article Description</b>	<b>Q-E-1733g/m<sup>2</sup>-1270mm LEO Coated</b>
<b>Textile Structure</b>	-	<b>LEO®</b>	

### ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal Weight	Tolerance		Material
5	0°	319 g/m <sup>2</sup>	5 %		E-Glass 900 tex
4	45°	300 g/m <sup>2</sup>	5 %		E-Glass 300 tex
3	90°	307 g/m <sup>2</sup>	5 %		E-Glass 600 tex
2	-45°	300 g/m <sup>2</sup>	5 %		E-Glass 300 tex
1	Leo Coating	500 g/m <sup>2</sup>	10 %		Leo Coating
Stitching		7 g/m <sup>2</sup>	+/- 2 g/m <sup>2</sup>		Polyester (PES) 83 dtex

### FURTHER CHARACTERISTICS

Gauge	5	Stitching Pattern	Tricot	Width (nominal)	1270 mm
Stitch length	2,6 mm	Total tolerance	7,4 %	Total areal weight	1733 g/m <sup>2</sup>

Labelling (Standard)	Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.
Packaging (Standard)	Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.
Storage recommendation	With original packaging: No moisture and direct sunlight. To avoid problems with humidity and electrostatic charge, fabrics to be conditioned 24 hours prior to processing, independent of storage conditions.

SAERTEX GmbH & Co. KG has been certified in accordance with ISO 9001:2015 and has been awarded the 2018 Eco-Profit Award. The SAERTEX GmbH & Co. KG has its own DNV GL certified laboratory.

**REINFORCING YOUR IDEAS**