

TECHNICAL DATASHEET

SAP No. 30012987 **Article Description** B-C-604g/m²-1270mm

Textile Structure 7009777 **SAERTEX®**

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
2	0 °	299 g/m ² 8.82 oz/yd ²	+/- 5.0 %	HYOSUNG H2550 A-Size 12K
1	90 °	299 g/m ² 8.82 oz/yd ²	+/- 5.0 %	HYOSUNG H2550 A-Size 12K
Stitching		6 g/m ² 0.18 oz/yd ²	+/-1 g/m ² +/-0.03 oz/yd ²	PES [Polyester] 76 dtex

FURTHER CHARACTERISTICS

Gauge	5.0	Stitching pattern	tricot	Width (nominal)	1270 mm
Stitch length	3.50 mm	Total tolerance	5.1 %	Total areal weight	604 g/m ² 17.8 oz/yd ²

Labelling (Standard) Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard) Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage (recommendation) Keep in original packaging. Store in a dry environment. Avoid direct sunlight. Fabrics to be kept under processing conditions at least 24 hours prior to use to avoid problems with humidity and electrostatic charge.