

TECHNICAL DATASHEET

SAP No. 30017114 **Article Description** B-S-E-1540g/m²-1270mm

Textile Structure 7011465 **SAERTEX®**

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
3	0 °	614 g/m ² 18.11 oz/yd ²	+/- 5.0 %	E-glass 1,200 TEX
2	90 °	614 g/m ² 18.11 oz/yd ²	+/- 5.0 %	E-glass 1,200 TEX
1	CSM	300 g/m ² 8.85 oz/yd ²	+/- 10.0 %	Boron free glass
Stitching		12 g/m ² 0.35 oz/yd ²	+/-3 g/m ² +/-0.09 oz/yd ²	PES [Polyester] 110 dtex

Fiber input can be determined individually

FURTHER CHARACTERISTICS

Gauge	7.0	Stitching pattern	tricot-warp	Width (nominal)	1270 mm
Stitch length	4.00 mm	Total tolerance	6.1 %	Total areal weight	1540 g/m ² 45.4 oz/yd ²

Labelling (Standard) Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard) Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage (recommendation) Keep in original packaging. Store in a dry environment. Avoid direct sunlight. Fabrics to be kept under processing conditions at least 24 hours prior to use to avoid problems with humidity and electrostatic charge.