

TECHNICAL DATASHEET

SAP No. 30016221 Article Description SAERcore 300/RC18/300 - 1250mm

Textile Structure 7011059

SAERcore®

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
3	CSM	300 g/m ²	+/- 10,0 %	E-glass
2	Core	180 g/m ²	+/- 10,0 %	Recycled Synthetic Core
1	CSM	300 g/m ²	+/- 10,0 %	E-glass
Stitching		7 g/m ²	+/- 2 g/m ²	Polyamid 6.6 122 dtex

Fiber input can be determined individually

FURTHER CHARACTERISTICS

Gauge	3,5	Stitching pattern	tricot	Width (nominal)	1250 mm
Stitch length	5,00 mm	Total tolerance	+/- 10,2 %	Total areal weight	787 g/m ²

Labelling (Standard) Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard) Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage (recommendation) Keep in original packaging. Store in a dry environment. Avoid direct sunlight. Fabrics to be kept under processing conditions at least 24 hours prior to use to avoid problems with humidity and electrostatic charge.

Important advice The Z side of the stitching line should be placed preferably on the cosmetic face to obtain the best surface finish.