

TECHNICAL DATASHEET

SAP No. 30004044 Article Description U-C-603g/m²-1230mm

Textile Structure 7003743

SAERTEX®

ARTICLE CONSTRUCTION (in accordance with EN 13473-1)

Layer	Construction	Areal weight	Tolerance	Material
3	0 °	581 g/m ²	+/- 5,0 %	Carbon
2	-60 °	8 g/m ²	+/- 5,0 %	E-glass
1	60 °	8 g/m ²	+/- 5,0 %	E-glass
Stitching		6 g/m ²	+/- 1 g/m ²	synthetic

FURTHER CHARACTERISTICS

Gauge	5,0	Stitching pattern	tricot	Width (nominal)	1230 mm
Stitch length	3,00 mm	Total tolerance	+/- 5,1 %	Total areal weight	603 g/m ²

Labelling (Standard) Every roll is equipped with a label in the core. A further label is located outside on the foil or on the box.

Packaging (Standard) Every roll is wound on a cardboard core and wrapped in foil. Further packaging options can be determined individually.

Storage (recommendation) Keep in original packaging. Store in a dry environment. Avoid direct sunlight. Fabrics to be kept under processing conditions at least 24 hours prior to use to avoid problems with humidity and electrostatic charge.